

AGEOTEC

powered by



CALZONI

# Pegaso

Multipurpose ROV



## KEY FEATURES

- Thrusters: 2 vertical and 4 vectored state of the art Ageotec TK4 DC brushless
- Operating depth: 2000 m with TMS (1200 m free-flight)
- Dimensions: 1800 mm (L) x 1100 mm (W) x 1300 mm (H)
- Weight in air: 800 kg
- Chassis: High Impact Resistant Maintenance Free Polyethylene
- 3 Video channels: Zoom, focus and still camera controls provided as standard
- 4 single mode fiber optic channels
- 4 x LED lamps
- Power requirements: 400÷440VAC 3-phase 50÷60Hz 45kW for 600 m umbilical
- Payload: Adjustable between 40 kg and 60 kg (up to 150 kg with hydraulic tools)
- Manipulators: 2/4 or 5/6 functions mounted on skid

### STRUCTURE/FRAME AND FITTING

Modular chassis manufactured in high impact resistant Polyethylene maintenance free and non-corroding. Any chassis member can be easily replaced and additional equipment may be bolted directly onto it. Hard stainless steel AISI 316 loading frame and lift points. All pressure housings are manufactured in Aluminium Anticorodal 6060

### PROPULSION

2 vertical and 4 horizontal state of the art vectored Ageotec TK4 DC brushless thrusters, magnetic coupling.  
· Vertical thrust 110 kg  
· Forward thrust 140 kg  
· Lateral Thrust 100 kg

### PAYLOAD

Adjustable between 40 kg and 60 kg with manipulator skid up to 150 Kg

### UMBILICAL

2000 m with TMS (1200 m free-flight)

### BUOYANCY

Glass reinforced epoxy floating with apertures provided for 2 acoustic positioning transponders

### UNDERWATER TOOLS / MANIPULATORS

One or two multifunctional manipulators up to 6 function, skid mounted

### CAMERA / VIDEO / LIGHTING

3 video channels. Zoom, focus and still camera controls provided as standard.  
2 x 400 LED lamps lighting line and 2x24VDC led lamps lighting line with intensity control are available as standard on two individually controlled channels.  
Pan&Tilt with feedback position displayed on pilot monitor is standard. Joystick's control provides an accurate control

### NAVIGATION / TRACKING

Fluxgate compass unit with solid state rate gyro sensor featuring high azimuth stability; Electronic depth sensor. Standard functions: Auto-heading and Auto-depth. Optional function auto-altitude with altimeter

### OPERATIONAL DEPTH RATING

2000 m

### DEPLOYMENT SYSTEM

Options include: LARS (Launch and Recovery System); TMS (Tether Management System); ROV control cabin

### VEHICLE POWER REQUIREMENTS

400 VAC 3-phase 50 Hz 45Kw 3-phase outlet skid and TMS (other versions on request)

### OPERATING / MAINTENANCE CREW

2/3 persons

### DEPLOYMENT MODE

Options include: LARS (Launch and Recovery System); TMS (Tether Management System); ROV control cabin

### OPTIONS

- Optional Cathodic Protection (CP) Probe
  - Inertial Navigation System
  - Multi-beam Echosounders
  - Panoramic sonar
  - Dual head profiler system
  - Bathymetric system
  - Altimeter
  - Pipe Tracker
- All measurements can be displayed on pilot monitor

Custom configurations available on request

### SYSTEM DIMENSIONS

	VEHICLE	6 U CONSOLE		METAL CABINET
		w. cover	w/o cover	Power Cabinet
Length (mm)	1800	550	540	800
Width (mm)	1100	770	570	600
Height (mm)	1300	320	310	1400
Weight in Air (kg)	800	-	22.0	400



subject to change without notice\*

### Headquarters & Sales:

Via Prati 1/1 - Località Ponte Ronca, 40069 Zola Predosa - Bologna, Italy  
phone: +39 051 6133382 - fax: +39 051 6136159

[www.ageotec.com](http://www.ageotec.com)

powered by  CALZONI